



MOMANSAGLUE

DESCRIPTION

MOMANSAGLUE is inflammable, heat Resistant, one component adhesive purely on **POLYCHLOROPRENE** with special resins, Tackifier and additives. It is specially developed For Nitral, EPDM rubber closed cell and PE Cross Link foam Insulation system.

PROPERTIES

MOMANSAGLUE has correct balance of wet And dry tack with smooth flow properties and Uniform and fast drying characteristics. **MOMANSAGLUE** is heaving very good heatAnd fire retardant properties and it is completelyFire resistance in cured form.

APPLICATION

MOMANSAGLUE has excellent adhesion andGood compatibility with closed cell NitralRubber, EPDM and PE crosslink foamInsulation with range of metal substrate and nonMetal surfaces. Porous Substrates like Leather, Leather Board.

USES

Used for Air Duct insulation, Pipe sections, Slabs, under deck (metal sealing)Leather, Leather Boerd etc.

DIRECTION OF USE

Before applying, the surface should be prepare Clean and even, free from dust loose shavings, oil and grease.

Apply **MOMANSAGLUE** on both surfaces, either with brush or pressure feeding equipment to a uniform coat.

Allow 10-20 minutes to evaporate the complete Solvent, and then assemble the surface by Applying normal hand pressure to give strong Bond.

OPEN TIME

Open time varies for surface from 10 minutes to 25 minutes depending on thickness of layers of Adhesive, substrate type, moisture and Temperature.

COVERAGE

The wet coverage of **MOMANSAGLUE** is 6 to 8 m2 /kg subjected to the applied film Thickness. The recommended film thickness is 100 to 120 mic. To get proper coverage, please Always keep close the container's spout toPrevent the solvent evaporation

CAUTION

Adequate ventilation must be maintained, Particularly in confined spaces. Due to volatilein nature of solvent, keep away from source of Ignition such as pilot lights or sparks. Prohibition of smoking must be rigidly enforcedin the vicinity of use. Do not open lid of Container use spout only, to prevent and Minimize the evaporation.

STORAGE & SHELF LIFE

Store under cover, protect from direct sunlightAnd high temperature (>205C). Shelf life is up to12 months in unopened container when stored as directed. Failure to comply with the recommended Storage conditions may result in premature. Deterioration of the product or packaging.Please follow the petroleum regulation and law of the land.

CLEANING

Clean all the tools with aromatic solvent.

PACKING

MOMANSAGLUER is available in 25 litter Spouted Metal Pai.

HEALTH & SAFETY

As with all chemicals, caution should always be Exercised. Protective clothing such as gloves and Goggles should be worn.

INHALATION: Inhalation of vapour or mist should be Avoided. k Symptoms include coughing, wheezing, Laryngitis, and shortness of breath, headache, nausea, And vomiting. Immediately shift victim to fresh air, and, if needed immediately start artificial respiration. Give Oxygen if breathing is laboured. Get emergency medical Help.

EYE CONTACT: Flush eyes with water for 15 minutes and call for medical help.

INGESTION: causes nausea, vomiting, and loss of Consciousness. If accidentally swallowed do not induce Vomiting rather call for medical help immediately.

SKIN CONTACT: Flush with water or soap and water Until all traces have been removed. Seek medical Attention if required.

TECHNICAL DATA

Base	CR
No. of component	One
Colour	Black/ Yellow pale/ Brown
Solid	24%
Viscosity	000 cps (brook field)
Density	0.82+-0.02
Service Temp.	-20°C to + 120°C
Flash Point	22°C
Water Resistance	Excellent
Chemical resistance	Good
Application tools	Brush, Roller and Airless spray
Solubility	Hydrocarbon

WARRANTY

Page.... 2 of 2

All information is given in good faith on the result gained from experience and test. However, all recommendation or suggestions are made without guarantee since manufacturer does not have any control on site conditions and its uses.